



Certificate of Compliance

Product	Rated Capacity, (gal/min)	Rated Capacity, (dm ³ /min)	Rated Net Head at Rated Capacity, psi	Rated Net Head at Rated Capacity, kPa	Rated Speed, r/min	Suction Inlet, dia., in.	Discharge Outlet, dia., in.	Stage(s)
WF-6x4x10 HS	400	1515	134-197	925-1360	3500	6	4	1
WF-6x4x10 HS	450	1705	134-196	925-1350	3500	6	4	1
WF-6x4x10 HS	500	1895	134-197	925-1360	3500	6	4	1
WF-6x4x10 HS	750	2840	134-197	925-1360	3500	6	4	1
WF-6x4x10 HS	1000	3785	126-196	870-1350	3500	6	4	1
WF-6x4x12 HS	750	2840	125-196	860-1350	2800	6	4	1
WF-6x4x12 HS	1000	3785	116-194	800-1340	2800	6	4	1
WF-6x4x12 HS	1000	3785	126-209	870-1440	2900	6	4	1
WF-6x4x12 HS	1000	3785	130-217	895-1495	2950	6	4	1
WF-6x4x12 HS	1000	3785	135-224	930-1545	3000	6	4	1
WF-6x4x12 HS	400	1515	218-310	1505-2135	3500	6	4	1
WF-6x4x12 HS	450	1705	218-309	1505-2130	3500	6	4	1
WF-6x4x12 HS	500	1895	218-308	1505-2125	3500	6	4	1
WF-6x4x12 HS	750	2840	215-311	1480-2145	3500	6	4	1
WF-6x4x12 HS	1000	3785	208-309	1435-2130	3500	6	4	1
WF-6x4x17 HS	500	1895	230-295	1585-2035	2800	6	4	1
WF-6x4x17 HS	750	2840	225-281	1550-1935	2800	6	4	1
WF-6x4x17 HS	1000	3785	192-259	1325-1785	2800	6	4	1
WF-6x4x17 HS	500	1895	247-317	1705-2185	2900	6	4	1
WF-6x4x17 HS	750	2840	242-304	1670-2095	2900	6	4	1
WF-6x4x17 HS	1000	3785	222-280	1530-1930	2900	6	4	1
WF-6x4x17 HS	500	1895	256-328	1765-2260	2950	6	4	1
WF-6x4x17 HS	750	2840	250-315	1725-2170	2950	6	4	1
WF-6x4x17 HS	1000	3785	230-292	1585-2015	2950	6	4	1
WF-6x4x17 HS	500	1895	265-340	1825-2345	3000	6	4	1
WF-6x4x17 HS	750	2840	259-326	1785-2250	3000	6	4	1
WF-6x4x17 HS	1000	3785	240-303	1655-2090	3000	6	4	1
WF-8x5x11 HS	750	2840	122-183	840-1260	2800	8	5	1
WF-8x5x11 HS	1000	3785	117-181	805-1250	2800	8	5	1
WF-8x5x11 HS	1250	4730	111-175	765-1205	2800	8	5	1
WF-8x5x11 HS	1500	5680	105-168	725-1160	2800	8	5	1
WF-8x5x11 HS	750	2840	131-197	905-1360	2900	8	5	1
WF-8x5x11 HS	1000	3785	126-194	870-1340	2900	8	5	1
WF-8x5x11 HS	1250	4730	120-189	825-1305	2900	8	5	1
WF-8x5x11 HS	1500	5680	114-182	785-1255	2900	8	5	1
WF-8x5x11 HS	750	2840	135-204	930-1405	2950	8	5	1
WF-8x5x11 HS	1000	3785	131-201	905-1385	2950	8	5	1



Member of the FM Global Group



Certificate of Compliance

Product	Rated Capacity, (gal/min)	Rated Capacity, (dm ³ /min)	Rated Net Head at Rated Capacity, psi	Rated Net Head at Rated Capacity, kPa	Rated Speed, r/min	Suction Inlet, dia., in.	Discharge Outlet, dia., in.	Stage(s)
WF-8x5x11 HS	1250	4730	124-196	855-1350	2950	8	5	1
WF-8x5x11 HS	1500	5680	119-189	820-1305	2950	8	5	1
WF-8x5x11 HS	750	2840	140-210	965-1450	3000	8	5	1
WF-8x5x11 HS	1000	3785	135-208	930-1435	3000	8	5	1
WF-8x5x11 HS	1250	4730	130-203	895-1400	3000	8	5	1
WF-8x5x11 HS	1500	5680	124-195	855-1345	3000	8	5	1
WF-8x5x11 HS	750	2840	194-277	1340-1910	3500	8	5	1
WF-8x5x11 HS	1000	3785	190-277	1310-1910	3500	8	5	1
WF-8x5x11 HS	1250	4730	185-270	1275-1860	3500	8	5	1
WF-8x5x11 HS	1500	5680	177-265	1220-1820	3500	8	5	1
WF-8x6x11 HS	1500	5680	104-153	715-1055	2900	8	6	1
WF-8x6x11 HS	2000	7570	100-149	690-1025	2900	8	6	1
WF-8x6x11 HS	1500	5680	108-159	745-1095	2950	8	6	1
WF-8x6x11 HS	2000	7570	104-154	715-1060	2950	8	6	1
WF-8x6x11 HS	1500	5680	111-164	765-1130	3000	8	6	1
WF-8x6x11 HS	2000	7570	108-159	745-1095	3000	8	6	1
WF-8x6x11 HS	1500	5680	149-191	1030-1320	3500	8	6	1
WF-8x6x11 HS	2000	7570	144-190	995-1310	3500	8	6	1
WF-8x6x14 HS	1500	5680	135-188	930-1300	2800	8	6	1
WF-8x6x14 HS	2000	7570	124	855	2800	8	6	1
WF-8x6x14 HS	1500	5680	146-203	1010-1400	2900	8	6	1
WF-8x6x14 HS	2000	7570	135-192	930-1320	2900	8	6	1
WF-8x6x14 HS	1500	5680	152-210	1050-1450	2950	8	6	1
WF-8x6x14 HS	2000	7570	140-200	965-1380	2950	8	6	1
WF-8x6x14 HS	1500	5680	157-218	1080-1500	3000	8	6	1
WF-8x6x14 HS	2000	7570	146-207	1010-1430	3000	8	6	1



Member of the FM Global Group



Certificate of Compliance

Product	Rated Capacity, (gal/min)	Rated Capacity, (dm ³ /min)	Rated Net Head at Rated Capacity, psi	Rated Net Head at Rated Capacity, kPa	Rated Speed, r/min	Suction Inlet, dia., in.	Discharge Outlet, dia., in.	Stage(s)
WF-5x3x10HS	300	1135	80-133	550-915	2800	5	3	1
WF-5x3x10HS	300	1135	87-143	600-985	2900	5	3	1
WF-5x3x10HS	300	1135	89-147	615-1015	2950	5	3	1
WF-5x3x10HS	300	1135	93-153	640-1055	3000	5	3	1
WF-5x3x10HS	300	1135	91-209	625-1440	3500	5	3	1
WF-5x3x10HS	400	1515	76-130	525-895	2800	5	3	1
WF-5x3x10HS	400	1515	82-140	565-965	2900	5	3	1
WF-5x3x10HS	400	1515	87-145	600-1000	2950	5	3	1
WF-5x3x10HS	400	1515	88-206	605-1420	3500	5	3	1
WF-5x3x10HS	400	1515	89-150	615-1035	3000	5	3	1
WF-6x4x12HS	400	1515	111-168	765-1160	2600	6	4	1
WF-6x4x12HS	400	1515	128-192	880-1325	2800	6	4	1
WF-6x4x12HS	400	1515	138-206	950-1420	2900	6	4	1
WF-6x4x12HS	400	1515	142-213	980-1470	2950	6	4	1
WF-6x4x12HS	400	1515	147-220	1015-1515	3000	6	4	1
WF-6x3x14HS	400	1515	182-220	1255-1515	2950	6	3	1
WF-6x3x14HS	400	1515	188-228	1295-1570	3000	6	3	1
WF-5x3x10HS	450	1705	74-129	510-890	2800	5	3	1
WF-5x3x10HS	450	1705	80-138	550-945	2900	5	3	1
WF-5x3x10HS	450	1705	84-144	580-995	2950	5	3	1
WF-5x3x10HS	450	1705	86-205	595-1415	3500	5	3	1
WF-5x3x10HS	450	1705	87-149	600-1025	3000	5	3	1
WF-6x4x12HS	450	1705	111-168	765-1160	2600	6	4	1
WF-6x4x12HS	450	1705	128-192	880-1325	2800	6	4	1
WF-6x4x12HS	450	1705	138-206	950-1420	2900	6	4	1
WF-6x4x12HS	450	1705	142-213	980-1470	2950	6	4	1
WF-6x4x12HS	450	1705	147-220	1015-1515	3000	6	4	1
WF-5x3x10HS	500	1895	72-128	495-885	2800	5	3	1
WF-5x3x10HS	500	1895	78-137	540-945	2900	5	3	1
WF-5x3x10HS	500	1895	81-142	560-980	2950	5	3	1
WF-5x3x10HS	500	1895	83-202	570-1395	3500	5	3	1
WF-5x3x10HS	500	1895	84-147	580-1015	3000	5	3	1
WF-6x4x12HS	500	1895	111-168	765-1160	2600	6	4	1
WF-6x4x12HS	500	1895	128-192	880-1325	2800	6	4	1
WF-6x4x12HS	500	1895	138-206	950-1420	2900	6	4	1
WF-6x4x12HS	500	1895	142-213	980-1470	2950	6	4	1
WF-6x4x12HS	500	1895	147-220	1015-1515	3000	6	4	1



Member of the FM Global Group



Certificate of Compliance

<i>Product</i>	<i>Rated Capacity, (gal/min)</i>	<i>Rated Capacity, (dm³/min)</i>	<i>Rated Net Head at Rated Capacity, psi</i>	<i>Rated Net Head at Rated Capacity, kPa</i>	<i>Rated Speed, r/min</i>	<i>Suction Inlet, dia., in.</i>	<i>Discharge Outlet, dia., in.</i>	<i>Stage(s)</i>
WF-6x3x14HS	500	1895	172-211	1185-1455	2950	6	3	1
WF-6x3x14HS	500	1895	179-220	1235-1515	3000	6	3	1
WF-8x4x16HS	500	1895	220-265	1515-1825	2900	8	4	1
WF-8x4x16HS	500	1895	229-274	1580-1890	2950	8	4	1
WF-8x4x16HS	500	1895	237-284	1635-1960	3000	8	4	1
WF-6x4x12HS	750	2840	104-164	715-1130	2600	6	4	1
WF-6x4x12HS	750	2840	132-204	910-1405	2900	6	4	1
WF-6x4x12HS	750	2840	136-211	940-1455	2950	6	4	1
WF-6x4x12HS	750	2840	142-218	980-1505	3000	6	4	1
WF-8x4x16HS	750	2840	208-250	1435-1725	2900	8	4	1
WF-8x4x16HS	750	2840	215-260	1480-1795	2950	8	4	1
WF-8x4x16HS	750	2840	223-269	1540-1855	3000	8	4	1
WF-8x4x16HS	1000	3785	192-233	1325-1605	2900	8	4	1
WF-8x4x16HS	1000	3785	200-242	1380-1670	2950	8	4	1
WF-8x4x16HS	1000	3785	208-252	1435-1735	3000	8	4	1



Member of the FM Global Group