

QXXW.EX28268 - CENTRIFUGAL FIRE PUMPS, VERTICAL TURBINE

Centrifugal Fire Pumps, Vertical Turbine

See General Information for Centrifugal Fire Pumps, Vertical Turbine

WATERFALL PUMPS MANUFACTURING

EX28268

Al_T-tay, Warehouse no. 1-5, Plot No.2840764, PO Box 371219

Dubai, UNITED ARAB EMIRATES

Rated Capacity gpm	Model Dsg	Rated Net Pressure Range psi	Approx Speed rpm	Stages
150	WF-8F2 VT	59-230	2600	3-9
150	WF-8F2 VT	68-268	2800	3-9
150	WF-8F2 VT	73-288	2900	3-9
150	WF-8F2 VT	76-268	2950	3-9
150	WF-8F2 VT	79-308	3000	3-9
200	WF-8F2 VT	57-227	2600	3-9
200	WF-8F2 VT	67-263	2800	3-9
200	WF-8F2 VT	72-283	2900	3-9
200	WF-8F2 VT	74-293	2950	3-9
200	WF-8F2 VT	77-303	3000	3-9
250	WF-8F2 VT	55-224	2600	3-9
250	WF-8F2 VT	64-262	2800	3-9
250	WF-8F2 VT	69-282	2900	3-9
250	WF-8F2 VT	72-292	2950	3-9
250	WF-8F2 VT	72-292	2950	3-9
250	WF-8F2 VT	75-302	3000	3-9
250	WF-9F2 VT	55-271	2600	2-6
250	WF-9F2 VT	64-314	2800	2-6
250	WF-9F2 VT	69-338	2900	2-6

250	WF-9F2 VT	71-349	2950	2-6
250	WF-9F2 VT	74-361	3000	2-6
300	WF-8F2 VT	53-220	2600	3-9
300	WF-8F2 VT	62-257	2800	3-9
300	WF-8F2 VT	67-277	2900	3-9
300	WF-8F2 VT	70-288	2950	3-9
300	WF-8F2 VT	72-298	3000	3-9
300	WF-9F2 VT	55-267	2600	2-6
300	WF-9F2 VT	64-312	2800	2-6
300	WF-9F2 VT	69-335	2900	2-6
300	WF-9F2 VT	71-348	2950	2-6
300	WF-9F2 VT	74-360	3000	2-6
300	WF-12F4 VT	100-120	1480	5
300	WF-12F4 VT	128-240	1480	6-10
300	WF-12F4 VT	103-124	1500	5
300	WF-12F4 VT	131-248	1500	6-10
300	WF-12S4 VT	145-348	1750	5-10
300	WF-12S4 VT	148-360	1780	5-10
400	WF-8F2 VT	81.00	2800	3
400	WF-8F2 VT	102.00	2800	4
400	WF-8F2 VT	131.00	2800	5
400	WF-8F2 VT	153.00	2800	6
400	WF-8F2 VT	189.00	2800	7
400	WF-8F2 VT	204.00	2800	8
400	WF-8F2 VT	233.00	2800	9
400	WF-8F2 VT	62-265	2900	3-9
400	WF-8F2 VT	64-275	2950	3-9
400	WF-8F2 VT	67-286	3000	3-9
400	WF-9F2 VT	53-262	2600	2-6
400	WF-9F2 VT	62-306	2800	2-6
400	WF-9F2 VT	68-330	2900	2-6

400	WF-9F2 VT	70-342	2950	2-6
400	WF-9F2 VT	73-354	3000	2-6
400	WF-12F2 VT	87-295	2600	2-4
400	WF-12F2 VT	102-347	2800	2-4
400	WF-12F2 VT	110-374	2900	2-4
400	WF-12F2 VT	115-388	2950	2-4
400	WF-12F2 VT	119-402	3000	2-4
400	WF-12F4 VT	100-236	1480	5-10
400	WF-12F4 VT	100-243	1500	5-10
400	WF-12S4 VT	137-334	1750	5-10
400	WF-12S4 VT	145-346	1780	5-10
450	WF-9F2 VT	49-257	2600	2-6
450	WF-9F2 VT	60-302	2800	2-6
450	WF-9F2 VT	65-325	2900	2-6
450	WF-9F2 VT	68-337	2950	2-6
450	WF-9F2 VT	71-349	3000	2-6
450	WF-12F2 VT	88-286	2600	2-4
450	WF-12F2 VT	101-339	2800	2-4
450	WF-12F2 VT	108-367	2900	2-4
450	WF-12F2 VT	112-381	2950	2-4
450	WF-12F2 VT	116-396	3000	2-4
450	WF-12F4 VT	100-115	1480	5
450	WF-12F4 VT	123-231	1480	6-10
450	WF-12F4 VT	100-238	1500	5-10
450	WF-12S4 VT	137-332	1750	5-10
450	WF-12S4 VT	145-344	1780	5-10
500	WF-9F2 VT	84.00	2600	2
500	WF-9F2 VT	118.00	2600	3
500	WF-9F2 VT	161.00	2600	4
500	WF-9F2 VT	203.00	2600	5
500	WF-9F2 VT	247.00	2600	6

500	WF-9F2 VT	99.00	2800	2
500	WF-9F2 VT	148.00	2800	3
500	WF-9F2 VT	198.00	2800	4
500	WF-9F2 VT	247.00	2800	5
500	WF-9F2 VT	291.00	2800	6
500	WF-9F2 VT	61-320	2900	2-6
500	WF-9F2 VT	64-332	2950	2-6
500	WF-9F2 VT	67-345	3000	2-6
500	WF-12F2 VT	84-282	2600	2-4
500	WF-12F2 VT	100-331	2800	2-4
500	WF-12F2 VT	109-357	2900	2-4
500	WF-12F2 VT	113-370	2950	2-4
500	WF-12F2 VT	117-385	3000	2-4
500	WF-12F4 VT	100-113	1480	5
500	WF-12F4 VT	122-226	1480	6-10
500	WF-12F4 VT	100-116	1500	5
500	WF-12F4 VT	125-233	1500	6-10
500	WF-12S4 VT	137-327	1750	5-10
500	WF-12S4 VT	145-339	1780	5-10
750	WF-12F2 VT	77-257	2600	2-4
750	WF-12F2 VT	92-305	2800	2-4
750	WF-12F2 VT	100-330	2900	2-4
750	WF-12F2 VT	104-343	2950	2-4
750	WF-12F2 VT	108-355	3000	2-4
750	WF-12F4 VT	94-215	1480	5-10
750	WF-12F4 VT	97-222	1500	5-10
750	WF-12S4 VT	129-154	1750	5
750	WF-12S4 VT	165-307	1750	6-10
750	WF-12S4 VT	136-159	1780	5
750	WF-12S4 VT	171-318	1780	6-10
750	WF-14F4 VT	75-92	1480	3

750	WF-14F4 VT	100-216	1480	4-7
750	WF-14F4 VT	77-95	1500	3
750	WF-14F4 VT	102-222	1500	4-7
750	WF-14S4 VT	101-129	1750	3
750	WF-14S4 VT	143-302	1750	4-7
750	WF-14S4 VT	105-134	1780	3
750	WF-14S4 VT	149-313	1780	4-7
1000	WF-12F2 VT	91-314	2950	2-4
1000	WF-12F2 VT	95-326	3000	2-4
1000	WF-12S4 VT	120-292	1750	5-10
1000	WF-12S4 VT	124-304	1780	5-10
1000	WF-14F4 VT	72-87	1480	3
1000	WF-14F4 VT	96-202	1480	4-7
1000	WF-14F4 VT	74-89	1500	3
1000	WF-14F4 VT	99-208	1500	4-7
1000	WF-14S4 VT	100-126	1750	3
1000	WF-14S4 VT	138-294	1750	4-7
1000	WF-14S4 VT	101-131	1780	3
1000	WF-14S4 VT	143-305	1780	4-7
1000	WF-16F4 VT	65-83	1480	2
1000	WF-16F4 VT	98-249	1480	3-6
1000	WF-16F4 VT	67-85	1500	2
1000	WF-16F4 VT	100-256	1500	3-6
1000	WF-16S4 VT	91-117	1750	2
1000	WF-16S4 VT	136-292	1750	3-5
1000	WF-16S4 VT	94-121	1780	2
1000	WF-16S4 VT	141-302	1780	3-5
1250	WF-14F4 VT	69-83	1480	3
1250	WF-14F4 VT	92-194	1480	4-7
1250	WF-14F4 VT	71-86	1500	3
1250	WF-14F4 VT	95-200	1500	4-7

1250	WF-14S4 VT	100-122	1750	3
1250	WF-14S4 VT	134-286	1750	4-7
1250	WF-14S4 VT	100-127	1780	3
1250	WF-14S4 VT	139-297	1780	4-7
1250	WF-16F4 VT	62-81	1480	2
1250	WF-16F4 VT	93-244	1480	3-6
1250	WF-16F4 VT	64-84	1500	2
1250	WF-16F4 VT	96-251	1500	3-6
1250	WF-16S4 VT	88-114	1750	2
1250	WF-16S4 VT	132-285	1750	3-5
1250	WF-16S4 VT	91-118	1780	2
1250	WF-16S4 VT	137-296	1780	3-5
1500	WF-14F4 VT	80.00	1500	3
1500	WF-14F4 VT	106	1500	4
1500	WF-14F4 VT	133	1500	5
1500	WF-14F4 VT	152	1500	6
1500	WF-14F4 VT	182	1500	7
1500	WF-14S4 VT	97-114	1750	3
1500	WF-14S4 VT	129-267	1750	4-7
1500	WF-14S4 VT	100-119	1780	3
1500	WF-14S4 VT	134-278	1780	4-7
1500	WF-16F4 VT	58-79	1480	2
1500	WF-16F4 VT	88-236	1480	3-6
1500	WF-16F4 VT	60-81	1500	2
1500	WF-16F4 VT	90-243	1500	3-6
1500	WF-16S4 VT	88-112	1750	2
1500	WF-16S4 VT	132-280	1750	3-5
1500	WF-16S4 VT	91-116	1780	2
1500	WF-16S4 VT	136-290	1780	3-5
2000	WF-16F4 VT	52-74	1480	2
2000	WF-16F4 VT	78-221	1480	3-6

2000	WF-16F4 VT	54-76	1500	2
2000	WF-16F4 VT	81-228	1500	3-6
2000	WF-16S4 VT	83-109	1750	2
2000	WF-16S4 VT	125-274	1750	3-5
2000	WF-16S4 VT	86-114	1780	2
2000	WF-16S4 VT	129-284	1780	3-5

+ This pump can be fitted with a suction vessel for inlet pressures not exceeding 100 psi.

++ This pump can be fitted with a suction vessel for inlet pressures not exceeding 200 psi.

Last Updated on 2020-01-14

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2020 UL LLC"